

Submitted in 09/986,809




PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : H02K 49/04	A1	(11) International Publication Number: WO 97/35377 (43) International Publication Date: 25 September 1997 (25.09.97)
<p>(21) International Application Number: PCT/US97/03949</p> <p>(22) International Filing Date: 13 March 1997 (13.03.97)</p> <p>(30) Priority Data: 08/617,314 18 March 1996 (18.03.96) US</p> <p>(71) Applicant: MAGNA FORCE, INC. [US/US]; 2602 West 18th, Port Angeles, WA 98363 (US).</p> <p>(72) Inventor: LAMB, Karl, J.; 944 Monroe Road, Port Angeles, WA 98363 (US).</p> <p>(74) Agents: SEED, Richard, W. et al.; Seed and Berry L.L.P., 6300 Columbia Center, 701 Fifth Avenue, Seattle, WA 98104-7092 (US).</p>	<p>(81) Designated States: AL, AM, AT, AU, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report.</p>	

(54) Title: PERMANENT MAGNET BRAKING SYSTEM



(57) Abstract

A conductor rotor (15) presents a pair of electroconductive rings (16, 17) spaced apart to receive magnet carrying shoes (40, 40') with permanent magnets (42) to induce eddy currents in the rings and thereby retard rotation of the conductor rotor. The shoes are moved in and out in a controlled manner to move between a retracted brake-off position and an extended brake-on position.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon	KR	Republic of Korea	PL	Poland		
CN	China	KZ	Kazakhstan	PT	Portugal		
CU	Cuba	LC	Saint Lucia	RO	Romania		
CZ	Czech Republic	LI	Liechtenstein	RU	Russian Federation		
DE	Germany	LK	Sri Lanka	SD	Sudan		
DK	Denmark	LR	Liberia	SE	Sweden		
EE	Estonia			SG	Singapore		

Description

PERMANENT MAGNET BRAKING SYSTEM

5 Cross-Reference

This application is a continuation-in-part of my copending application Serial No. 08/546,066, filed October 20, 1995, which is a continuation of the application issued as Patent No. 5,477,094 issued December 19, 1995, which is a continuation-in-part of the application issued as Patent No. 5,477,093 issued
10 December 19, 1995.

Technical Field

This invention relates to braking systems for braking one of the rotors in a permanent magnet drive system of the general type shown in my Patent No.
15 5,447,094.

Background of the Invention

In my Patent No. 5,473,209 there is disclosed a permanent magnet braking system for a shaft having a magnet rotor thereon which co-acts with one or
20 two non-rotary electro-conductive members which can be adjusted in a direction axially of the shaft to vary the air gap between the magnet rotor and the electro-conductive member(s). When the air gap is narrowed a braking effect occurs.

A need has arisen for an alternative permanent magnet braking system which does not operate by varying the width of the air gap.
25

Summary of the Invention

The brake of the present invention operates in conjunction with a conductor rotor having a pair of electroconductive rings spaced apart axially of the rotor. The brake presents a pair of non-rotary magnet carrying shoes each extending
30 laterally from a respective laterally movable beam which is parallel to the rotary axis of the conductor rotor. Outward movement of the beams from a retracted inactive position places sets of permanent magnets on the shoes between a pair of the

electroconductive rings and spaced therefrom by air gaps. As a result the magnetic flux emanating from the magnets is intersected by the rotating electroconductive rings and eddy currents are created therein. Consequently the rotational speed of the conductor rotor is retarded. The amount of retardation can be varied by varying the amount of overlap of the magnets by the electroconductive rings, and namely by varying the outward extension of the magnet carrying shoes by the beams as by pneumatic cylinders.

Brief Description of the Drawings

10 Fig. 1 is a longitudinal horizontal sectional view of a braking system embodying the invention and with the brake being shown in an "off" position;

Fig. 2 is a transverse sectional view taken as indicated by line 2-2 in Fig. 1;

Fig. 3 is a sectional view corresponding to Fig. 1, but with the brake being shown in a fully "on" position; and

Fig. 4 is a transverse sectional view taken as indicated by line 4-4 in Fig. 3 and with parts broken away.

Detailed Description of the Invention

20 Referring to the drawings, shafts 10-11 are connected by couplings 12-13 to a magnet rotor unit 14 and conductor rotor unit 15. The conductor rotor unit presents two axially spaced flat rings (continuous bands) 16-17 having good electroconductive characteristics such, for example, as copper or aluminum. These rings 16-17 have ferrous backing rings 18-19, preferably of mild steel. The ferrous backing 18-19 for the electroconductive rings 16-17, and the electroconductive rings 25 16-17, are mounted on a support ring 15a and a support plate 15b having a hub 15c receiving the coupling 13. Spacers in the form of sleeves 22 separate the members 15a-15b and they are held by bolts 23 passing through the sleeves and the members 15a-15b.

30 The support members 15a-15b are formed with like annular recesses of a thickness to receive respective of the backing rings 18-19 and electroconductive

rings 16-17 in stacked relation. It is preferred to have the mouth of the recesses countersunk with a pattern of indentations matching lobes 24 provided on an expanded outer border portion of the electroconductive rings 16-17 which extends beyond the outer marginal edge of the backing 18-19. Mounting screws extend
5 through holes 24a in the lobes 24 into the support members 15a-15b.

Acting in concert with the conductor rotor 15 is a pair of magnet shoes 40-40'. The shoe 40 has, for example, three magnet sets 42 mounted in rectangular through openings 43 in the shoe. Each magnet set 42 has a pair of permanent magnets 42a, 42b arranged with their polarities reversed relative to one another.

10 The shoes 40-40' are mounted on beams 44-44' which are parallel to and diametrically opposite from the rotary axis of the shaft 11. The beams 44-44' are selectively moved toward and away from the rotary axis by operation of pneumatic cylinders 46-46' acting against respective cross-members 48-48' each of which interconnects a respective pair of guide rods 50-51 and 50'-51'. These guide rods
15 extend through linear bearings 52 mounted together with the inner end of the cylinders 46-46' on a suitable rigid frame (not shown).

Referring to Fig. 4 it is seen that the magnet sets 42 in each shoe 40-40' are arranged in an arc which corresponds to the curvature of the electroconductive rings 16-17. When the shoes are extended to a fully "on" condition of the brake (Figs.
20 3-4), the longitudinal side faces of the magnets in each set 42 which face one another define a neutral plane 42' therebetween which extends radially from the rotary axis 54 of the shaft 11 for maximum performance of the magnets.

When the cylinder 46-46' are in a retracted condition the magnet carrying shoes 40-41' are retracted toward one another to an "off" position where the
25 magnet sets 42 are withdrawn from between the electroconductive rings 16-17 (Figs. 1-2). When the brake is to be applied the cylinders 46-46' are energized to extend the cylinder rods 46a-46a' and push the cross-members 48-48' outwardly. Control of the cylinders 46-46' can be performed by a control system coupled to a suitable compressed air supply as well known in the pneumatic control art and as shown, for
30 example, in Patent No. 5,473,209. When the cross-members 48-48' move outwardly the pairs of guide rods 50-51 and 50'-51' are pulled outwardly through the linear

bearings 52, thereby moving the beams 44-44' and shoes 40-40' outwardly so that the sets of magnets 42 move between the rotating electroconductive rings 16-17. As this movement occurs, eddy currents are induced in the rings 16-17 by the magnetic fields of the magnets. As a consequence rotation of the conductor 15 is progressively retarded with outward advancement of the shoes 40-40' increasing exposure of the magnet sets 42 to the rings 16-17.

It will be understood that the conductor rotor 16 may have an additional pair of electroconductive rings mounted on the outer side of the mounting ring 18 and an additional mounting ring spaced therefrom by additional spacers 22 and carried on longer tie bolts 23. When that is done additional magnet carrying shoes can be mounted on the beams 44-44' to interact with the additional pair of electroconductive rings.

The parts 15a, 22, 15b and 15c of the conductor rotor 15, and the shoes 40-40' and beams 44-44' are preferably made of a suitable aluminum alloy.

From the foregoing it will be appreciated that, although specific embodiments of the invention have been described herein for purposes of illustration, various modifications may be made without deviating from the spirit and scope of the invention. Accordingly, the invention is not limited except as by the appended claims.

Claims

1. A braking system comprising:
a conductor rotor having a rotary axis and two axially spaced electroconductive rings;
a non-rotating braking shoe presenting permanent magnets each with its poles facing in opposite axial directions; and
means for selectively moving said shoe between a brake-off position not between said rings and a brake-on position between said rings for inducing eddy currents in the rings when the conductor rotor is rotating.
2. A braking system according to claim 1 in which there are a pair of said shoes positioned diametrically opposite one another relative to said axis.
3. A braking system according to claim 1 in which said shoe has multiple magnets occupying an arc corresponding generally to the curvature of said rings.
4. A braking system according to claim 1 in which said shoe is mounted on a member which is parallel to said axis and is spaced inwardly toward said axis from said rings, said means including a mechanism for selectively moving said member outwardly toward said rings and inwardly toward said axis.
5. A braking system according to claim 1 in which the movement of said shoe between brake-off and brake-on positions is along a linear path perpendicular to said axis.
6. A braking system according to claim 1 in which said rings are backed with mold steel bands and are mounted in aluminum members.

7. A braking system according to claim 4 in which said member is rigidly mounted on a pair of guide rods slideably mounted in stationary bearings.




Fig. 1






Fig. 2

2/2

*Fig. 3**Fig. 4*

SUBSTITUTE SHEET (RULE 26)

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 97/03949

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H02K49/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 H02K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X Y A	DE 934 296 C (BAERMANN) 20 October 1955 see the whole document	1,4,5 2,3,6 7
Y	--- PATENT ABSTRACTS OF JAPAN vol. 009, no. 018 (M-353), 25 January 1985 & JP 59 164424 A (MAGUNE KK), 17 September 1984, see abstract	2
Y	--- FR 1 505 384 A (MIJNHARDT) 22 February 1968 see page 2, right-hand column, line 54 - page 3, left-hand column, line 10; figure 3 --- -/--	3

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

1 July 1997

Date of mailing of the international search report

09.07.97

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Zanichelli, F

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 97/03949

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	FR 2 102 600 A (SOCIÉTÉ D'ÉTUDES ET DE RECHERCHES MAGNÉTIQUES) 7 April 1972 see page 2, line 25 - page 3, line 14; figure 1 ---	6
X	DE 925 414 C (BAERMANN) 21 March 1955 see page 4, line 32 - line 43; figure 2 ---	1,5
A	US 5 051 638 A (PYLES NATHAN) 24 September 1991 see figures 3-5 ---	3
A	DE 16 13 022 A (BAERMANN) 23 December 1970 see figures ---	3
A	WO 94 28614 A (LAMB KARL J) 8 December 1994 cited in the application see figures -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 97/03949

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 934296 C		NONE	
FR 1505384 A	22-02-68	NL 6508252 A DE 1541145 A US 3442131 A	27-12-66 09-10-69 06-05-69
FR 2102600 A	07-04-72	AT 311136 A,B BE 771097 A CA 939718 A CS 166030 B DE 2139009 A GB 1362423 A NL 7110946 A SE 372609 B	15-09-73 09-02-72 08-01-74 29-01-76 17-02-72 07-08-74 15-02-72 23-12-74
DE 925414 C		NONE	
US 5051638 A	24-09-91	NONE	
DE 1613022 A	23-12-70	NONE	
WO 9428614 A	08-12-94	US 5477093 A AU 678834 B AU 6915594 A BR 9406542 A EP 0699358 A JP 8510894 T NO 954680 A US 5473209 A US 5477094 A	19-12-95 12-06-97 20-12-94 02-01-96 06-03-96 12-11-96 20-11-95 05-12-95 19-12-95